


**MAXIMA**

**SERIE H**

SUPPORTO NYLON GRIGIO RAL 7005  
 GREY POLYAMIDE CASTOR RAL 7005



PORTATA - LOAD CAPACITY **Kg. 90 - 120**

Ruota in gomma grigia antitraccia scorrevole su cuscinetti a sfere a tenuta stagna DIN 625. Disponibile anche con ruota in poliuretano. Supporto stampato in nylon fibra di vetro girevole su cuscinetto a sfere di precisione DIN 625 2RS a tenuta stagna. Colore grigio RAL 7005.

Ruote sciolte vedi pag. 154  
 156

Grey rubber tyre non-marking on water proof original ball bearing DIN 625. Available also with non marking polyurethane wheel. Moulded fiber glass polyamide housing swivel on water proof precision ball bearing DIN 625 2RS. Grey colour RAL 7005.

Wheels only see pag. 154  
 156



**RUOTA GIREVOLE  
 SWIVEL CASTOR**



ART.



**FRENO TOTALE  
 TOTAL BRAKE**




ART.




**FRENO DIREZIONALE  
 DIRECTIONAL LOCK**



ART.

	mm	mm		mm	mm	Kg. (da N)				
<b>RUOTA IN GOMMA                      GRIGIA ANTITRACCIA</b>  <b>NON-MARKING GREY                      RUBBER TYRE</b> 	100	32		145	38	90		<b>H170GFS100*</b>	<b>H470GFS100*</b>	<b>H870GFS100*</b>
	125	32		165	47	100		<b>H170GFS125*</b>	<b>H470GFS125*</b>	<b>H870GFS125*</b>
	150	32		195	49	120		<b>H170GFS150*</b>	<b>H470GFS150*</b>	<b>H870GFS150*</b>
	200	32		251	67	120		<b>H170GFS200*</b>	<b>H470GFS200*</b>	<b>H870GFS200*</b>

<b>RUOTA IN POLIURETANO                      GRIGIO ANTITRACCIA</b>  <b>NON-MARKING                      POLYURETHANE TYRE</b> 	100	32		145	38	100		<b>H170DNS100*</b>	<b>H470DNS100*</b>	<b>H870DNS100*</b>
	125	32		165	47	100		<b>H170DNS125*</b>	<b>H470DNS125*</b>	<b>H870DNS125*</b>
	150	32		195	49	120		<b>H170DNS150*</b>	<b>H470DNS150*</b>	<b>H870DNS150*</b>
	200	32		251	67	120		<b>H170DNS200*</b>	<b>H470DNS200*</b>	<b>H870DNS200*</b>

Indicare la misura di fissaggio richiesta Es. H170GFS125FB1

Please indicate the requires size of fitting Es. H170GFS125FB1

**\*SISTEMI DI ATTACCO \*TYPE OF FITTINGS**

**\*SISTEMI DI ATTACCO \*TYPE OF FITTINGS**



**FORO PASSANTE  
 BOLT HOLE**  
 Q12 - Ø12  
  
**FORO FILETTATO  
 THREADED HOLE**  
 QM10 - M10  
 QM12 - M12



**ATTACCO FILETTATO  
 THREADED STEM**  
  
 FB1 - M10x20  
 FB3 - M12x20



**ESPANSORE ZAMA  
 ALU EXPANDER**  
 EBZ1 - Ø17-18,5  
 EBZ2 - Ø19-21,5  
 EBZ3 - Ø22-23,5  
 EBZ4 - Ø24-27,5  
 EBZ6 - Ø28-32  
 EBZ7 - J20-20



**ESPANSORE IN NYLON  
 POLYAMIDE EXPANDER**  
  
 EBN2 - Ø19-20  
 EBN3 - Ø20,5-22  
 EBN4 - Ø22-24  
 EBN5 - Ø25-26



**ATTACCO CILINDRICO  
 STEEL STEM**  
 C2 - Ø19x45  
 C3 - Ø20,5x45  
 C4 - Ø21,5x45  
 C5 - Ø22x45  
 C7 - Ø25,5x45  
 C8 - Ø27,5x45



**PIASTRA  
 PLATE**  
  

	AxB	axb	G
PQ	80x80	60x60	Ø8,5
PR	90x70	70x50	Ø8,5
PD	77x67	60x50	Ø8,5